



P861_{4x4}

TECHNICAL DATASHEET

The P861 LED luminaire excels in optical performance, thermal management, compatibility and serviceability, bringing an uncompromised outcome of efficiency and versatility that is future-proofed for an optimised investment

The P861 has been designed to meet the most demanding lighting requirements, being easy to install and maintain. It combines latest LED light source with state-of-the-art design, achieving long life for both LEDs and the drivers. The installation is simple and fast, and the luminaire is easily upgradable on-site if required.




SPECIFICATION



| | |
|-------------------------------|--|
| Light Source | High Power CSP LEDs |
| Number of LEDs | 256 (128 x 2) |
| Power Consumption | 75 - 360W |
| Correlated Colour Temperature | Neutral white, 4000K (Warm 3000K option) |
| Glare Class | Up to G6 |
| Colour Rendering Index | >70 |
| Optical Cover | Flat Glass - Tested to IK09 |
| Luminaire Luminous Flux | 11000 - 58640lm |
| Luminaire Efficacy | Up to 165 lm/W |
| Electrical Class | I |
| Control System Input | 1-10V and DALI |
| Lumen Maintenance Output | L90 > 100,000 hours (1050mA, Ta = 25°C) |
| Driver Current | 200mA - 1050mA in 25mA steps |
| Surge Protection | 10kV Com. Mode 6 kV Diff. Mode to IEC 61000-4-5 |
| Dimming Control | Dynadimmer |
| Lighting Regulation | Mini Photocell, ANSI 7-pin NEMA, Zhaga Book 18 socket(s), Wireless CMS options |
| Operating Temperature | -40°C to +50°C |
| Raised Ambient Operation | +50°C (up to 500mA driver current) |
| Installation Height | 8 - 15m |
| Installation | SE Ø 34-42mm or Ø 42-60mm PT Ø 42-60mm or Ø 60-76mm |
| Post Top / Side Entry Tilt | -10°, -5°, 0°, 5°, 10° |
| Material | High pressure die cast aluminium (housing) |
| Finish | Polyester powder coat cured under heat |
| Colours | Light Grey (RAL 7035), other RAL colours available on request |
| Ingress Protection | IP66 |
| Wind Area (SCx) | 0.042m ² |
| Weight | 14.5kg |

P861_{4x4}



TECHNICAL DATASHEET




42mm Side Entry



60mm Side Entry



76mm Post Top



Available accessories :-

- Safety lanyard
- Bubble level
- External shields, front, back and sides
- Internal rear shield
- Bird spikes